

STORTH

EXPERTS IN SLURRY MANAGEMENT



Specialist Manufacturers of
**Slurry handling
equipment**



Tel: +44 (0) 1524 781 900

Email: info@storthmachinery.co.uk

www.storthmachinery.co.uk

SCRAPE IT PUMP IT STORE IT MIX IT SPREAD IT



Mega Mix Lagoon Pump with Side Discharge Pipe

- 150mm or 200mm side discharge pipe allows for pumping out of lagoons
- Hydraulic ram controls mixing depth
- PTO shaft included (All star tubes)
- Jetter rotates 300 degrees
- 150 - 200HP required



Kite Hydraulic Mixer

- 5 metre standard length
- 900mm propeller giving excellent mixing capability
- Hooks for securing the top of the mixer to a quick fastening system (not supplied)
- Angle of propeller can be adjusted for maximum mixing efficiency
- Minimum oil flow 100 litres per minute

Hawk Tank Mixer

- Full hydraulic movement via remote control
- Fully Galvanised
- PTO included
- 160 - 200HP required
- Two lower jettors, one top jetter
- Optional 150mm discharge pipe for pumping out into tankers
- Special models available on request, with interior pump longer than the vertical column to suit tanks where the base level is below ground level.





Superjet Pump 3 Point Linkage

- 125mm & 150mm options available
- Under Surface Agitator for mixing
- Male Bauer fitted to outlet
- PTO included
- No need to disconnect PTO when moving from pit to pit
- 540 RPM Heavy Duty Gearbox
- 80-100 HP required
- Adjustable model for mixing different depth pits

Hydraulic Kit Option allows full control of ALL pump movements from the tractor



Electric Pump Static

- Under Surface Agitator for mixing
- Male Bauer fitted to outlet
- 11kW - 22kW motors available
- 100 to 125mm Male Bauer options



Centrifugal Chopper Pump

- Tractor PTO or direct engine coupling drive the impellor and cutting system.
- Hardened steel cutting mechanisms work in conjunction with an open impellor design to deliver slurry containing partially macerated solids to the pipe and flexible hose system



Farmer Bobbin Reeler

- Fully Galvanised (Inc Bobbin & Frame Panel)
- Std Female A Frame & 3 Point Linkage Coupling
- Hydraulic Hose Parking
- Robust Build
- 80mm Box 5mm Wall
- 25mm Chain Drive
- Motor Chain Tensioner
- 55mm Bobbin Axle
- Full Width Square Coupling Trough (optional)
- Bolt In Bobbin Reel Dividers



Combi Mounted Reeler

- Fully Galvanised (Inc Bobbin Sides)
- HD Female A Frame & 3 Point Linkage Coupling
- Hydraulic Hose Parking
- 80mm Box 5mm Wall Thickness
- HD Gearbox Drive c/w Cross Valve Relief
- 55mm Bobbin Axle
- Full Width Square Coupling Trough
- Single Hose Tension Roller
- HD Pin Lock Collar Guide
- LED Lights



Trailing Shoe

- Fully Galvanised
- Vertical Fold Arms
- Self-Sharpening Novatek Macerator
- 50mm Outlets on Macerator
- Heavy Duty Springs
- 225mm Spacings
- Shoe Castings Blued for long life
- Robust Rubber Boots
- Hydraulic Gate Valve Control



Vertical Fold Dribble Bar

- Fully Galvanised
- Vertical Folding
- Self-Sharpening Novatek Macerator
- 40mm Macerator Outlets
- 50mm Feed Pipes
- 250mm Spacing
- Drag Hose Application



Engine Pump Station

- FPT 175hp Engine
- Integral Bunded Fuel Tank 800lt
- Skid Unit with Pallet Tine Engagement
- Manual Control Panel
- Bauer SX2000 Direct Drive Pump
- Self-Contained Primer including Generator
- Full Circulation System
- Manual Control & Automatic Control options